






NeoFlow Pressure reducing valve POM-C DN50 - DN150 / Set pressure range 1 - 8 bar

- Nominal pressure: PN16
- Connection type: Wafer Design
- Sealing material: EPDM
- Body material: POM-C
- Components: Stainless Steel, Brass
- Medium: Water
- Co-developed with OFUI



d	DN	PN	min Pressure	max Pressure	Body	Code	Weight
(mm)	(mm)	(bar)	(bar)	(bar)			(kg)
63	50	16	1.0	8.0	POM-C	193 173 011	4.7
90	80	16	1.0	8.0	POM-C	193 173 013	6.0
100	100	16	1.0	8.0	POM-C	193 173 014	6.8
160	150	16	1.0	8.0	POM-C	193 173 017	10.7

D	Lmax	L1	L2	Hmax	Wmax
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
105	290	42.5	78.5	265	245
142	290	57.0	78.0	322	274
162	290	76.5	78.5	322	286
218	290	125.0	80.5	339	346



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>